

Features: (typical values)

- Wide Band 1000-3000 MHz.
- Noise Figure 3.0 dB.
- High Gain 52 dB.

Maximum Ratings

| | |
|---------------------|-----------------|
| Storage Temperature | -62°C to +125°C |
| DC Voltage | +17 volts |
| RF Input Power | +7.0 dBm. |
| Case Temperature | +100°C |

Specifications (Referenced to 50 ohms)

| Parameter | Typical Conditions | Min Value | Max Value | Units |
|--|--------------------|-----------|-----------|-------|
| Frequency | | 1000 | 3000 | MHz. |
| Gain | 52 | 50 | | dB. |
| Gain Flatness | ±0.5 | | ±1.5 | dB. |
| Gain Var. over temp | 0.6 | | | ΔdB. |
| Pout @ 1dB Comp | +26 | +24 | | dBm. |
| Noise Figure | 3.0 | | 4.5 | dB. |
| Reverse Isolation | 60 | | | dB. |
| IP ₃ /IP ₂ (two-tone)* | 38/44 | 35/40 | | dBm. |
| HIP2 (2 nd harm.) | 45 | | | dBm. |
| VSWR In/Out | 1.7:1 | | 2.0:1 | |
| Supply Required | +15/1600 | | +15/1700 | v/mA. |

Min. and max. values are from -55°C to +85°C

*IP3 and IP2 are in band output intercept points

