


**Features: (typical values)**

- Wide Band ..... 10-1000 MHz.
- Noise Figure ..... 3.0 dB.
- High Gain ..... 42 dB.

**Maximum Ratings**

- Storage Temperature ..... -62°C to +125°C  
 DC Voltage ..... +17 volts  
 RF Input Power ..... +7.0 dBm.  
 Case Temperature ..... +100°C

Specifications (Referenced to 50 ohms)

**10-1000 MHz  
Cascadable Amplifier**


Parameter	Typical Conditions	Min Value	Max Value	Units
Frequency		10	1000	MHz.
Gain	42	40		dB.
Gain Flatness	±0.5		±1.0	dB.
Gain Var. over temp	0.6			ΔdB.
Pout @ 1dB Comp	+26	+25		dBm.
Noise Figure	3.0		4.5	dB.
Reverse Isolation	60			dB.
IP <sub>3</sub> /IP <sub>2</sub> (two-tone)*	40/47	37/40		dBm.
HIP2 (2 <sup>nd</sup> harm.)	55			dBm.
VSWR In/Out	1.7:1		2.0:1	
Supply Required	+15/550		+15/570	v/mA.

Min. and max. values are from -55°C to +85°C

\*IP3 and IP2 are in band output intercept points

