

## General Purpose RF Amplifier

- \* Operating Frequency : 5-1000 MHz
- \* Gain : 11 dB
- \* Noise Figure : 9.0 dB max



### Description:

#### ELECTRICAL SPECIFICATION @ VDD= + 15VDC; Temp. = 25°C, 50Ω System

Parameter	Symbol	Min	Typ	Max	Unit
Operating Frequency	BW	5		1000	MHz
Gain @ 5-20 MHz	MHz	10	10.5	11	dB
Gain @ 20-1000 MHz	MHz	10.5	11	11.5	
Gain Flatness	$\Delta G$		$\pm 0.5$	$\pm 1.0$	dB
Reverse Isolation	S12	14	16		dB
Noise Figure	NF		7.8	9	dB
Power Output P1dB	P1dB	14	16		dBm
Output 3rd Order Intercept Point	OIP3	22	25		dBm
Output 2nd Order Intercept Point	OIP2	32	35		dBm
VSWR in/out	S11/S22		1.8 :1	2.1 :1	Ratio
Operating Voltage	Vdc		15		Volt
Operating Current	Id		70	80	mA

#### MECHANICAL SPECIFICATION

Parameter	Description	Limits	Units
Dimension	TO-12		
RF Connectors IN/OUT	NONE		
DC Connector	NONE		
Cooling	NONE		

#### PROTECTIONS

RF Input Power	13 dBm	
Reverse Polarity Protection	None	
Load VSWR	Infinite up to 1W	
Stability	100% Tested	

#### ENVIROMENTAL CHARACTERISTICS

Parameter	Symbol	Min.	Typ.	Max.	Units
Operating Case Temperature	Tc	- 55°C		85°C	°C
Storage Temperature	Tstg	- 62C		125°C	°C

3009 Old State Road, Telford, PA 18969

Web: [www.amplifiersolutions.com](http://www.amplifiersolutions.com)  
 Email: [sales@amplifiersolutions.com](mailto:sales@amplifiersolutions.com)

Tel: 215-799-2561  
 Fax: 215-799-2563

Outline Drawing

