


RF Amplifier

- * Operating Frequency : 20-2800 MHz.
- * Gain : 35 dB.
- * P1dB 33 dBm.
- * High Gain available
- * No external components required



ELECTRICAL SPECIFICATION @ VDD= +28 VDC; Temp. = 25°C, 50Ω System

Parameter	Symbol	Min	Typ	Max	Unit
Operating Frequency	BW	20		2800	MHz.
Gain @100MHz	G	34	37		dB.
Gain @2500MHz	G	30	33		dB.
Gain Flatness	Δ G		±2.0	±2.5	dB.
Noise Figure	N.F.		5	7	dB.
P1dB @2000MHz	P1dB	33	34		dBm.
Power Sat @2500MHz	Psat	34	35		dBm.
VSWR In	VSWR1		2.0:1	2.5:1	Ratio
Operating Voltage	Vdc		28		Volt
Operating Current Idq	Idq		2000		mA.

MECHANICAL SPECIFICATION

Parameter	Description	Limits	Units
RF connector	SMA-F		
DC Pins	Feedthru		
Cooling	None		
Monitor Connector	None		

PROTECTION

	Max	Units
RF Input Power	7	dBm.
Reverse Polarity Protection	YES	
Load VSWR	Infinite up to 1W	
Stability	100% Tested	


ENVIRONMENTAL CHARACTERISTICS

Parameter	Symbol	Min.	Typ.	Max.	Units
Operating Case Temperature	Tc	0°C		50°C	°C
Storage Temperature	Tstg	- 55°C		120°C	°C

3009 Old State Road, Telford, PA 18969

Web: www.amplifiersolutions.com
 Email: sales@amplifiersolutions.com

Tel: 215-799-2561
 Fax: 215-799-2563



Note: TTL On/OFF Procedure

- 0V.....On
- +5V.....Off


Do Not Apply more than 5V at ENABLE Pin

3009 Old State Road, Telford, PA 18969

Web: www.amplifiersolutions.com
 Email: sales@amplifiersolutions.com

Tel: 215-799-2561
 Fax: 215-799-2563

FUNCTIONAL BLOCK DIAGRAM



3009 Old State Road, Telford, PA 18969

Web: www.amplifiersolutions.com
Email: sales@amplifiersolutions.com

Tel: 215-799-2561
Fax: 215-799-2563