

Low Noise RF Amplifier

- * Operating Frequency : 3900-4100 MHz.
- * Linear Power : +12 dBm.
- * Noise Figure : 1.8 dB.
- * Medium Gain : 30 dB.
- * No external components required



ELECTRICAL SPECIFICATION @ VDD= +12VDC; Temp. = 25°C, 50Ω System

Parameter	Symbol	Min	Typ	Max	Unit
Operating Frequency	BW	3900		4100	MHz.
Gain	G	28	30		dB.
Gain Flatness	ΔG		± 0.3	± 0.4	dB.
Reverse Isolation	S 12		-40		dB.
Noise Figure	NF		1.8	2	dB.
Power Output P1dB	P1dB	10	12		dBm.
Output 3rd Order Intercept Point	OIP3	20	22		dBm.
VSWR in/out	S11/S22		1.6 :1	2.0 :1	Ratio
Operating Voltage	Vdc		12		Volt
Operating Current	Id		130	150	mA.

MECHANICAL SPECIFICATION

Parameter	Description	Limits	Units
Dimension	2.5x1x.5		in.
RF Connectors IN/OUT	SMA-F		
DC Connector	Filtered DC		
Cooling	None		

PROTECTIONS

RF Input Power	-10 dBm. Max	
Reverse Polarity Protection	Optional	
Load VSWR		
Stability	100%	

ENVIROMENTAL CHARACTERISTICS


Parameter	Symbol	Min.	Typ.	Max.	Units
Operating Case Temperature	Tc	0		50°C	°C
Storage Temperature	Tstg	-40		100°C	°C

3009 Old State Rd, Telford, PA 18969

Web: www.amplifiersolutions.com
 Email: sales@amplifiersolutions.com

Tel: 215-799-2561
 Fax: 215-799-2563

Outline Drawing



3009 Old State Rd, Telford, PA 18969

Web: www.amplifiersolutions.com
Email: sales@amplifiersolutions.com

Tel: 215-799-2561
Fax: 215-799-2563

FUNCTIONAL BLOCK DIAGRAM

