

RF Amplifier

* Operating Frequency : 1200-1800 MHz

* Gain : 37 dB

* NF: 0.6dB

* P1dB: 15dBm

ELECTRICAL SPECIFICATION @ VDD= +5 VDC; Temp. = 25°C, 50Ω System

Parameter	Symbol	Min	Typ	Max	Unit
Operating Frequency	BW	1200		1800	MHz
Gain	G	35	37	40	dB
Gain Flatness	Δ G		±0.75	±1.0	dB
Noise Figure	N.F.		0.6	0.8	dB
Output Power	P 1dB	10	15		dBm
VSWR in/out	S11/S22		1.6:1	1.75:1	Ratio
Operating Voltage	Vdc		5		Volt
Operating Current	Id		150	200	ma

MECHANICAL SPECIFICATION

Parameter	Description	Limits	Units
Dimension	1.175(L) x 0.575(W) x 0.20(H)		
Hermetic Sealing	YES		
Cooling	None		
In/Out Connectors	SMA-F		

PROTECTION

		Max	
RF Input Power		-15	dBm
Reverse Polarity Protection	N/A		
Load VSWR	Infinite up to 1W		
Stability	100% Tested		

ENVIRONMENTAL CHARACTERISTICS

Parameter	Symbol	Min.	Typ.	Max.	Units
Operating Case Temperature	Tc	-10		55	°C
Storage Temperature	Tstg	- 20C		70°C	°C

3009 Old State Road Telford Pa 18969

Web: www.amplifiersolutions.com
 Email: sales@amplifiersolutions.com

Tel: 215-997-7856
 Fax: 215-997-7857

Outline Drawing

